

Four Glass Swing Door CounterLine

Range: BackBar
SKOPE ID: CL004
Dimensions: 2800 mm (W) × 680 mm (D) × 830 mm (H)*
Capacity: 721 L

Project: _____
Item #: _____

* Height with castors is adjustable from 820 to 835.



A glass door under-counter bar fridge designed to merchandise ready-to-serve cold beverages in bars, restaurants, clubs, pubs, and cafés. Engineered to serve cold drinks at 1°C to 4°C (or adjustable up to 15°C) in ambient environments of up to 40°C. Made from powder-coated, galvanised steel with colour options, it can also be upgraded to full stainless-steel construction. The 'frameless' glass doors provide maximum product viewing and are designed for condensation protection in most environments via the double-glazed, argon-filled low-e insulated panels and heated fascia. For high humidity tropical environments heated glass versions are available. The doors and cabinet are fitted with built-in retractable tabs to enable locking via padlock. The built-in LED lights provide optimum merchandising and can be dimmed or timed to turn on and off via a free smartphone app. The fridge uses R290 natural refrigerant for ultra-low energy consumption, low heat discharge and low noise output and can be provided in remote versions. The side-mounted fully removable refrigeration cartridge (with left and right options) is front-breathing and can be removed in line with best practice for safe servicing of flammable refrigerants. The fridge includes a controller that connects to a free app to enable the user to set temperatures and alerts, monitor temperatures and energy, and more. The fridge is certified to all Australian and New Zealand refrigeration and electrical safety standards.



Warranty




Natural Refrigerant



GEMS



SKOPE-connect



Cabinet

Type	CounterLine
Finish	Powdercoat galvanised steel or stainless steel
Insulation	Type PU foam
	Thickness (mm) 50
	Blowing Agent Cyclo-iso pentane (C5H10/C5H12)
Doors	Type Glass swing door (double glazed, low e, argon filled)
	Opening Size Height (mm) 538 Width (mm) 511
Shelving	Eight adjustable height plastic-coated wire shelves 4 x inner shelf (547W x 530D), 4 x outer shelf (605W x 530D)
Lighting*	2 x 16W, cool white (5500-6500K) LED strips on cabinet ceiling

Dimensions†

	External	Internal	Packed
Width (mm)	2800	2340	TBC
Depth (mm)	680	565	TBC
Height (mm)	830 (std. castors)	545	TBC
	725 (plinth mount)		
Weight (kg)	267		TBC
Capacity (L)	721		
Footprint (m²)	1.9		

Ventilation (mm)

Top	Sides	Rear
Not required	Not required	Not required

Product Loading

Facing	330 ml can	68	600 ml bottle	60
Loading	330 ml can	544	600 ml bottle	420

* Accessible via the free SKOPE-connect™ app.

† Allow for dimensional tolerances when installing the cabinet(s).

Performance

Product Temperature Range (°C)	1 to 4 (adjustable* from 0 to 15)
Maximum Ambient Temperature (°C)	40
Sound Level (dB(A))	Standard < 66
	Hush Mode* < 62

Greenhouse and Energy Minimum Standards (GEMS)

Star Rating	7
Product Temperature Class	M1 (-1 to 5°C)
Total Energy Consumption	4.21 kWh/24 h
Annual Running Costs	\$461 (@ \$0.30/kWh)

Electrical

Supply	220-240 volts a.c., 50 Hz, single phase supply
Cord	1.9 m power cord with 3-pin, 10 amp plug
Current draw (A)	4.0

Refrigeration

Controller	SCS Connect (SKOPE-connect™ compatible)
System Type	Removable cartridge
Cartridge Weight (kg)	24
Refrigerant/Charge	R290/81 g
Nominal Capacity (W)	850
Heat Rejection (W)	Average 175 Peak 215
Defrost Type	Automatic, off-cycle
Drainage	No plumbing required



CL.4.GSW
on the SKOPE website