

FAGOR 700 SERIES NATURAL GAS CHROME 2 ZONE FRY TOP WITH THERMOSTATIC CONTROL FTG-C-10L



Image is for illustrative purposes only © F.E.D.

The 700 Series offers functional solutions that improve product performance and introduces new and significant technical improvements, such as increased power for burners, ovens and grills. Always focused on improving and evolving, we've designed a series that is unbeatable in ergonomics, easy to use and, above all, easy to clean. All this combined with attractive styling, Fagor Industrial's experience and quality standards makes the 700 Series capable of the highest standards in performance.

DESCRIPTION

Fagor 700 series natural gas chrome 2 zone fry top with thermostatic control FTG-C7-10L

The Fagor Industrial 700 Series presents new styling, practical and efficient solutions and important improvements for users.

The 700 Series offers functional solutions that improve product performance and introduces new and significant technical improvements, such as increased power for burners, ovens and grills. Always focused on improving and evolving, we've designed a series that is unbeatable in ergonomics, easy to use and, above all, easy to clean. All this combined with attractive styling, Fagor Industrial's experience and quality standards makes the 700 Series capable of the highest standards in performance.

The 700 Series fry-tops have stainless steel burners with an ignition pilot light, and include a "Maximum-Minimum" type valve to control the burner flame and have thermostatic control of the plate temperature: 120 °C - 310 °C.

Made of stainless steel.

Burners in stainless steel with pilot.

Thermostat control of the hot-plate temperature 120 C° -310 C°.

Fully welded splash guard.

Smooth hot-plate. Surface area: 660 x 550 mm

50 microns thickness chromium coated steel sheeting hot-plate.

Easy ignition.

Fat collector under the grill.

Power: 14 kW or 50mj./h.

Dimensions: 700 x 780 x 290 mm.

SPECIFICATIONS

NET WEIGHT (KG)	72
WIDTH (MM)	700
DEPTH (MM)	780
HEIGHT (MM)	290
PACKING WIDTH (MM)	740
PACKING DEPTH (MM)	840
PACKING HEIGHT (MM)	590
POWER	14 kW or 50mj./h.