



Fagor EVO-CONCEPT undercounter dishwasher with drain pump CO-502BDD

Quick Overview

E-VO CONCEPT front-loading and under counter dishwasher with double wall door and body (EFFI-SILENT), and a 3-position robust compensated door, with recessed wash tank, recessed basket guides, tray filter and wash and rinse arms in AISI-304 stainless steel. Constant water consumption of 2.4 litres per cycle for the rinse with a mains pressure of 2 bar.

CO-502BDD is supplied with 1 dish rack and 1 glass rack (flat base).

- WaterMark approved

Description

Fagor EVO-CONCEPT undercounter dishwasher with drain pump detergent and rinse dispenser CO-502BDD

E-VO CONCEPT front-loading and under counter dishwasher with double wall door and body (EFFI-SILENT), and a 3-position robust compensated door, with recessed wash tank, recessed basket guides, tray filter and wash and rinse arms in AISI-304 stainless steel. Constant water consumption of 2.4 litres per cycle for the rinse with a mains pressure of 2 bar. New optimised hydraulic EFFI-WASH system, with stainless steel wash arms and one powerful 0.6 kW pump, guaranteeing a top quality effective and efficient wash with an optimum Sinner circle balance. It also has a built-in rinse aid dispenser and drainage pump (B) and detergent dispenser (DD) fitted at factory or supplied in kit form. It has adjustable feet to permit levelling according to the needs of the establishment. Magnetic door open sensor. Electromechanical control panel making it easy to use.

- Front loading dishwasher - EVO Generation - Concept range.
- Hourly production: 40 baskets/hour - 720 dishes/hour.
- Clearance (max ware height): 380 mm.
- Valid for GN-1/1 trays.
- Electronic control.
- Wash cycles: 90"-180".
- Made of stainless steel.
- Full Double skin body to isolate machine's noise from the environment. The door has double skin with special pressed isolation material, and stamped finishing to improve noise isolation and to keep the heat inside the machine. Rock counterbalanced door. Double spring and stainless steel hinge system. The case allows the placement of the machine under surfaces of 850 mm height.
- Double rotating wash and rinse systems, above and below, made of stainless steel.
- Tray filters on the tank, made of AISI-304 stainless steel.
- Supplied with 1 dish rack and 1 glass rack.
- Wash pump: 600 W.
- Drain pump: 30 W. Drainage cycle.
- Tank with 2.8 kW heating element.
- Tank capacity: 20 litres.
- Boiler with multipower heating elements: 1,8 / 2,8 / 3,7 / 5,6 kW, 15Amp
- Boiler capacity: 7 litres.

- Water consumption: 2.4 litres/rinse.
- Thermostatic temperature control: washing at 60°C and rinsing at 90°C.
- Thermostop.
- Security thermostats.
- Built-in automatic rinse dispenser.
- Built-in detergent doser.
- Built-in non-return valve.
- Safety magnetic switch for door opening.
- Adjustable legs.
- WaterMark approved

Water protection rating: IPX4

Total power: multipower 2,4 / 3,4 / 4,3 / 6,2 kW.

Dimensions: 600 x 600 x 830 mm.

Baskets equipment: 1 x CT-10, 1 x CP-16/18 and 2 cutlery containers.

1 Year Parts and Labour Warranty

Your Shipping Specifications

Net Weight (Kg)	60
Width (mm)	600
Depth (mm)	600
Height (mm)	830
Packing Width (mm)	690
Packing Depth (mm)	775
Packing Height (mm)	1105
Power	Multipower 2,4 / 3,4 / 4,3 / 22.32 MJ; 15Amp