LGT 3725

MediLine

	•
	1
	•

Gross/net capacity	350/332 litre	
Ext. dimensions in mm (w/d/h)	1378/789/915	
Int. dimensions in mm (w/d/h)	1170/500/650	
Energy consumption in 365 days	1069 kWh	
Climate rating	4 1	
Refrigerant	R 290	
Airborne acoustical noise emissions	55 dB(A)	
Connection Rating	3.0 A	
Voltage	220-240 V~	
Cooling system	static	
Defrosting	manual	
Temperature range	-10°C to -45°C	
Gradient *	4.3°C	
Max. fluctuation **	2.2°C	
Lid material	Steel	
Housing material/colour	steel/white	
Liner Material	white-coated aluminium	
Type of Control	electronic controller	
Temperature display	außen digital	
Interface	RS 485	
volt-free alarm contact	yes	
Maximum number of baskets	13	
Handle	aluminium shape	
Lock	fitted	
Insulation	100 mm	
Defrost water drain	yes	
Gross/net weight	80 / 68 kg	
EAN-Nr.	9005382201138	

1 Climate class / Climate $R\overline{a}$ ting: SN +10°C to +32°C

3 +10°C to +25°C

N +16°C to +32°C **4** +10°C to +30°C **ST** +16°C to +38°C **5** +10°C to +40°C

T +16°C to +43°C **7** +10°C to +35°C

^{*} Gradient as defined in EN 60068-3: the difference between the warmest and coldest average measurements, increased by their expanded uncertainty, throughout the duration.

*** Max. fluctuation as per EN 60068-3: greatest fluctuation value determined throughout the duration of measurements.