

# GKPx 6570

## ProfiLine



<b>Total gross capacity</b>	601 litre
<b>Ext. dimensions</b> in mm (w/d/h)	700/830/2150
<b>Int. dimensions</b> in mm (w/d/h)	510/650/1550
<b>Energy consumption</b> in 24 h	1,047 kWh
Climate rating <sup>1</sup>	T 5
Cooling system	forced-air
Defrosting	automatic
Temperature range	+1°C to +15°C
Gastronorm	530 x 650 mm
Housing material/colour	stainless steel/stainless steel
Door/lid material	Stainless steel
Liner Material	304-grade stainless steel
Type of control	electronic controller
Temperature display	external digital
Interior light	–
Fault: warning signal	visual and audible
Interface	–
volt-free alarm contact	yes
Shelves	5
Adjustable Shelving	4
Number of drawers	–
Number of baskets	–
Maximum number of baskets	–
Shelf material	grid shelves plastic-coated
Shelf loading	60 kg
Height of adjustable legs	120-170
Castors/type of castors	–
Door handle	full-length integrated door handle
Foot pedal opener	–
Self-closing door	yes
Insulation	83 - 60 mm
Defrost water drain	–
Refrigerant	R 290
Noise level	58 dB(A)
Gross/net weight	133/117 kg
EAN-Nr.	9005382170175

<sup>1</sup> Climate Ratings: **SN** +10°C to +32°C    **N** +16°C to +32°C    **ST** +16°C to +38°C    **T** +16°C to +43°C

Subject to modification. Timestamp: 23.03.2015

# LIEBHERR