

# FRFCvg 5501 Perfection (571)

## Forced-air refrigerator

Everything you could need to meet the highest demands and requirements of your everyday professional life. They are made of stainless steel, are available with either solid or glass doors, and feature optimal lighting. Their cooling range spans from  $-2$   $+15$  °C; their freezers include both the SmartFrost and the NoFrost functions.

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_


AIA # \_\_\_\_\_



### Your benefits

- Low total operating costs – from the compressor to the seal, to the lighting and electronics, Liebherr appliances fully utilise the savings potential of every component.
- In the event of an uncontrolled temperature rise, the interior light of the appliance starts flashing.
- The plastic-coated grid shelves allow versatile use of the interior and can support up to 60 kg.
- The self-closing door closes automatically from a 60° opening angle, preventing loss of cold air and ensuring ideal storage conditions for your goods.
- In commercial design, the deep drawn inner liner made of food-safe polystyrene is odour-neutral, very robust, and long-lasting.

Super Cool



#### Temperature range $-2$ °C/ $+15$ °C

Tasty for longer: Liebherr refrigerators have an extended temperature range from  $-2$  °C to  $+15$  °C – so even meat stays fresh and tasty for longer.



#### Replaceable door seal

Save time and money: Liebherr's plug-in door seals can be easily replaced. If a seal is damaged, you can replace it yourself without any tools.



#### LightAlarm

In case of an uncontrolled temperature rise, if a door has been left open or there were any other problems, the interior light of the appliance will start flashing. In the case of glass-door appliances, this quickly reveals when action is needed. In the case of solid-door appliances, the flashing interior warns to close the door immediately in order to preserve the storage quality.



#### Compatible with standard containers

Liebherr refrigerators for the catering industry are generally designed for use with Euro standard gastronomy containers. This means that any standard container used up to now will also fit in your new Liebherr.

# FRFCvg 5501 Perfection (571)

Forced-air refrigerator


## Specifications

|                                      |   |
|--------------------------------------|---|
| Gross/net capacity                   | 571/419 l                               |
| Ext. dimensions in mm (w/d/h)        | 747/769/1793                            |
| Int. dimensions in mm (w/d/h)        | 620/531/1442                            |
| Climate class (energy directive)     | 5                                       |
| Temperature class (energy directive) | M1                                      |
| Climate class (safety standard)      | 5                                       |
| Ambient temperature range            | +10 °C to +40 °C                        |
| Refrigerant                          | R 600a                                  |
| Connection Rating                    | 2.0 A                                   |
| Frequency / voltage                  | 50 Hz / 220-240 V~                      |
| Cooling system                       | forced-air                              |
| Defrosting                           | automatic                               |
| Temperature range                    | -2 °C to +15 °C                         |
| Housing material/colour              | stainless steel                         |
| Door material                        | steel                                   |
| Liner Material                       | moulded polystyrol (silver)             |
| Type of Control                      | monochrome display, touch buttons       |
| Temperature display                  | external digital                        |
| Interior light                       | LED ceiling lighting                    |
| Alarm in case of malfunction         | visual and audible                      |
| Connectivity type                    | SmartModule                             |
| Interface                            | WLAN/LAN (optional)                     |
| Adjustable Shelving                  | 5                                       |
| Shelf material                       | wire shelves plastic-coated             |
| Shelf loading                        | 60 kg                                   |
| Handle                               | aluminium handle                        |
| Castors                              | 2 fixed rear and 2 swivel front castors |
| Type of lock                         | mechanical                              |
| Self-closing door                    | yes                                     |
| Door hinges                          | right, reversible on site               |
| Gross/net weight                     | 87/77 kg                                |
| EAN-Nr.                              | 9005382277515                           |

Liebherr reserves the right to make modifications to the products without prior notice.  
All information are correct at the time of printing. 2024.06.24

The overview represents an excerpt of the most important appliance features.  
All other features of the appliance and further information  
are available at:

[home.liebherr.com/professional](https://home.liebherr.com/professional)

Follow us on 

**LIEBHERR**

# FRFCvg 5501 Perfection (571)

Technical drawing

