



<https://www.commercialfridgefreezer.com.au/thermoline-ti-250g-gravity-convection-premium-incubator/>

# Thermoline TI-250G Gravity Convection Premium Incubator 250L



Thermoline TI-250G Gravity Convection Premium Incubator 250L has an internal dimension of 500mm (W) x 520mm (D) x 970mm (H), an external dimension of 570mm (W) x 600mm (D) x 1200mm (H), a storage capacity of 250 litres, 4 shelves, and 400 watts of electricity.

## Description

Thermoline TI-250G Gravity Convection Premium Incubator 250L

### Features include:

- Stainless steel
- Easy to clean
- Corrosion resistant
- Adjustable open wire shelves
- Digital temperature display
- Temperature alarms

<https://www.commercialfridgefreezer.com.au/thermoline-ti-250g-gravity-convection-premium-incubator/>

Commercial Fridge and Freezer Sales Australia. All product images are provided for illustration purposes only. All specifications are subject to manufacturer changes without notice, so please check on the manufacturer's website for current product data.

- 13mm cable/ monitoring port hole with rubber plug
- Insulated external door
- Internal glass viewing door
- Gravity convection
- Auto overtemperature safety
- Over current protection
- Control error codes
- Open sensor detection
- Made in Australia

## Additional Information

Brand	Thermoline
Model	TI-250G
Temperature Operating Range C	5Â°C - 60Â°C
External Dimensions (mm)	570mm (W) x 600mm (D) x 1200mm (H)
Internal Dimensions (mm)	500mm (W) x 520mm (D) x 970mm (H)
Door Information	Solid door
About the Product	Thermoline TI-250G Gravity Convection Premium Incubator 250L temperature is maintained electronically between ambient 5 degrees to 60 degrees centigrade. Thermoline TI-250G has a safety controller.