



Turbo Air K-Series KR25-1-N(HC) Single Solid Door Top Mount Refrigerator

\$3,088.00 +GST

[View more Product Details](#)

[Add to Cart](#)

[Request a Quote](#)



Introducing the Turbo Air K-Series KR25-1-N(HC) Single Solid Door Top Mount Refrigerator, a reliable and efficient cooling solution for your business. Equipped with a Digital Temperature Control System and high-tech monitor, you have precise control over the inner temperatures ranging from 1° to 8°. The top-mounted design optimizes space utilization while the self-cleaning condenser ensures consistent performance. With HC(R290) Refrigerant and a hot gas condensate system, this refrigerator is environmentally friendly and energy efficient. The spacious capacity of 574L provides ample storage for your products. The ventilated cooling system and high-density polyurethane insulation guarantee optimal temperature distribution and retention.

Description

The Turbo Air K-Series KR25-1-N(HC) Single Solid Door Top Mount Refrigerator is a reliable and efficient refrigeration unit designed for commercial use. With its solid door and top-mounted configuration, this upright fridge offers convenient access and effective cooling performance.

Equipped with a digital temperature control system, you can easily adjust and monitor the internal temperature of the refrigerator to ensure optimal storage conditions. The high-tech monitor continuously tracks the operating status, providing real-time information and ensuring reliable performance.

Featuring a self-cleaning condenser, this refrigerator prevents dust accumulation and improves energy efficiency over time. It utilizes the environmentally friendly HC(R290) refrigerant, which is known for its low environmental impact. The hot gas condensate system helps prevent condensation and enhances the overall efficiency of the unit.

Turbo Air - Digital Temperature Control System
1 Solid door Upright Fridge
Top mounted
High-Tech Monitor
Self Cleaning Condenser Applied
HC(R290) Refrigerant applied
Hot Gas Condensate System
Capacity- 574L
Inner Temps 1 to 8
Ventilated Cooling
High-Density and CFC free Polyurethane Insulation
Adjustable, Heavy Duty, PE Coated Wire Shelves
Stainless steel exterior and Interior
Digital Controller and Display
Refrigerant R-290 Amps 2.0, Power-w 300
Dimensions 640x850x1926mm Inc Castors
Weight 77kg
220V-240v/50Hz/1, 10amp Australian Plug
3 Adjustable shelves included

Additional Information

Country of Manufacture	Asia
External Colour	Stainless Steel
Brand	Turbo Air
Model	KR25-1-N
Warranty	3 Years on Parts and Labour
Temperature Operating Range C	1°~8°
Temperature Display / Control	Digital control
Climate / Ambient Temperature Rating	35°
Refrigerant	R-290
External Dimensions (mm)	640 mm (W) x 850 mm (D) x 1926 mm (H)
Capacity/Volume	574
Other Details	Turbo Air Self Cleaning Condenser Upright Top Mount on castors
Power Usage	280W
Door Information	Door hinged = RH
Packaged Dimensions (mm)	686 mm (W) x 896mm (D) x 2015mm (H)
Interior Lighting	Yes
GEMS & MEPS Approved	Yes
Manufacturer's Suggested Retail Price	\$3,860.00